

LLIFE-SM-WP

CLEVERTRONICS L10 LIFELIGHT IP65 WEATHERPROOF SURFACE MOUNT EMERGENCY



Part Number	LLIFE-SM-WP				
MIC	UKD01320020001				
Description	L10 Optimum Lifelight, High Performance, Weatherproof, Surface Mounted Emergency Light Enabled with Clevertest Plus				
Construction	Polycarbonate Enclosure				
Mounting	Surface Mounted				
Dimensions L x W x H	247mm x 129mm x 51mm				
Weight	0.8kg				
Operating Mode	Non-maintained				
Testing System	Clevertest Plus Enabled (Not activated by default)				
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Lamp(s)	1×LED				
Operating Voltage	220-240V AC; 50Hz				
Total Lumen Output	180lm (Area Lens)				
Power Consumption	1.0W (Standby) 4.2W (Max)				
Rated Emergency Duration	180 minutes				
IP Rating	IP65				
IK Rating	IK08				
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)				
Operating temperature	0°C to 40°C				
Protection	Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts				
Luminaire Classification	Х	0	AD	180	
Conformity	BS EN 60598.2.22, BS 5266				

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice





LLIFE-SM-WP

CLEVERTRONICS L10 LIFELIGHT IP65 WEATHERPROOF SURFACE MOUNT EMERGENCY

REPLACEMENT PARTS			
PART NUMBER	DESCRIPTION		
1530071	BATTERY:L10 3.3V 2.5AH 200mm ld, no Brkt		
8050174	HWSUB: CT10694-D1 (Lifelight Head)		
8002905	PCA: LLIFE CT10260-L5 1C450 CTP UK Vert Connectors (Driver)		

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice

