



LLIFE-TRACK-D2-WHT

Lifelight, IP20, Emergency, Track Mount, L10 Nanophosphate, DALI-2 Emergency, White



PRODUCT INFORMATION

Catalogue Number	LLIFE-TRACK-D2-WHT
MIC	AUD01210170001
Description	Lifelight, IP20, Emergency, Track Mount, L10 Nanophosphate, DALI-2 Emergency, White
Construction	Polycarbonate Enclosure
Track Adapter	STUCCHI 9209/B, asymmetric 6 circuits adapter (3 Phase + Control System) with phase selector
Mounting	Track Mounted Note: check compatibility of Stucchi Adapter with the installed Track System. Unit may not function correctly if installed on incompatible Track Profile.
Dimensions L x W x H	See image on the next page
Weight	0.7 kg
Operating Mode	Non-maintained
Testing System	DALI-2
Battery Type	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x LED
Operating Voltage	220-240V AC; 50Hz
Power Connection	Track mounted – single circuit with DALI-2 (Da, Da) connections. Note: Final track adaptor configuration and DALI-2 connection to be confirmed prior to order placement
Total Lumen Output	180lm (Emergency)
Power Consumption	0.8 Watts (Standby), 2.8 Watts (Max)
Supply Current	43mA +/- 27mA
Inrush Current (Peak/Duration)	TBD
Earth Leakage	N/A
IP Rating	IP20
Operating temperature	1°C to 40°C
AS Classification	C0=D40, C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	Battery
2780072	LED
8003621	Driver
8003062	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order



LLIFE-TRACK-D2-WHT

Lifelight, IP20, Emergency, Track Mount, L10 Nanophosphate, DALI-2 Emergency, White

