



LLIFEM-PRO-HVG-BLK

Lifelight Pro Emergency, Recessed Mount, L10
Nanophosphate, Maintained, Zoneworks XT Hive, Black



PRODUCT INFORMATION	
Part Number	LLIFEM-PRO-HVG-BLK
MIC	UKT01810230001
Description	Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, Maintained, Zoneworks XT Hive, Black
Material	PC/ABS Head, double/reinforced insulation between supply and battery circuit of lamp control gear
Mounting	Surface Mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate)
Ceiling	Minimum Ceiling Depth 200mm or 120mm with adaptor plate Ceiling Hole Cut-Out 51mm or 85mm with adaptor plate
Weight	0.6kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Total Lumen Output	220lm (Maint), 357lm (EM)
Operating Voltage	220-240V AC; 50Hz
Battery	Lithium Nanophosphate (LiFePO ₄), Clevertronics
240V Driver	N/A
Charging Method	Intelligent Current Limited Constant Voltage
Power Consumption	2.7W (Standby), 5.0W (Max)
Power Factor	0.366W
Inrush Current (Max)	12.093A @87.3μS
Earth Leakage	0.311mA
IP Rating	IP20
IK Rating	N/A
Operating Temperature	0°C to 40°C
Max. casing temperature	50°C (no heatsink required for lamp control gear)
Rated Emergency Duration	180 Minutes
Luminaire Classification	X 1 ADF 180
Conformity	BS EN 60598-2-22, BS 5266
Compliance Marking	



LLIFEM-PRO-HVG-BLK

Lifelight Pro Emergency, Recessed Mount, L10
Nanophosphate, Maintained, Zoneworks XT Hive, Black

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533232	Battery
110-00010	LED Assembly
UKM01870040002 LLIFEM-PRO-CKIT-HVG	Emergency Driver
8003330	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order