



LLIFEM-PRO-SA-HVG-BLK

Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, Maintained, Switched Active, Zoneworks XT Hive, Black



PRODUCT INFORMATION	
Part Number	LLIFEM-PRO-SA-HVG-BLK
MIC	UKT01810350001
Description	Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, Maintained, Switched Active, Zoneworks XT Hive, , Black
Material	Polycarbonate Enclosure
Mounting	Ceiling Mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate)
Ceiling Hole Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)
Weight	0.6kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.7/3W/5W (STBY/MAIN/MAX)
Power Factor	0.65W
Inrush Current (Max)	12.093A @87.3µs
Earth Leakage	0.311mA
IP Rating	IP20
Operating Temperature	0°C to 40°C
Rated Emergency Duration	180 Minutes
Compliance Marking	UK CA CE
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)
Luminaire Classification	X 1 ADF 180
Conformity	BS EN 60598-2-22, BS 5266



LLIFEM-PRO-SA-HVG-BLK

Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, Maintained,
Switched Active, Zoneworks XT Hive, Black

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
8050260	LED Head Assembly
UKM01870530001 LLIFEM-PRO-SA-CKIT-HVG-415	Emergency Driver
8003330	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order