



## LLIFEM-PRO-SA-HVG

Lifelight Pro Emergency, Recessed Mount, L10  
Nanophosphate, Maintained, Switched Active, Zoneworks XT Hive



PRODUCT INFORMATION	
Part Number	LLIFEM-PRO-SA-HVG
MIC	UKT00000005601
Description	Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, Maintained, Switched Active, Zoneworks XT Hive
Material	Polycarbonate Enclosure
Mounting	Recessed Ceiling
Dimensions	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate)
Ceiling Hole Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)
Weight	0.6kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF) 2.4GHz
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	220-240V~ 50Hz
Total Lumen Output	357lm (Emergency), 220lm (Maintained)
Power Factor	0.65
Power Consumption	2.4W STBY/4.7W MAX
Inrush Current (Max)	12.093A @87.3µs
Earth Leakage	0.361mA
IP Rating	IP20
Rated Emergency Duration	180 Minutes
Operating Temperature	0°C to 40°C
Compliance Marking	
Luminaire Classification	X   1   ADF   180
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530232	Battery
1100897	240V LED Panel
UKM01870520001	Emergency Driver
8003330	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.