



LLIFEM-PRO-SA

L10 Optimum Maintained Lifelight PRO, Recessed Emergency Light,
Enabled with Clevertest Plus



PRODUCT INFORMATION

Part Number	LLIFEM-PRO-SA
MIC	AUT00000009701
Description	L10 Optimum Maintained Lifelight PRO, Recessed Emergency Light, Enabled with Clevertest Plus
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (98mm with adaptor plate)
Ceiling hole cut-out	51mm (85mm with adaptor plate)
Minimum ceiling depth	200mm (120mm with adaptor plate)
Operating Mode	Maintained (LEDs permanently ON at 250mA - 182lm, with no switch control) Emergency mode (LEDs running at 550mA - 336lm)
Testing System	Enabled with Clevertest Plus
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage charger
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	220-240V~50Hz
Power Consumption	2.4W (Standby), 4.7W (Max during 16-hour charge)
Inrush Current (Max)	12.093A / 87.3µs
Earth Leakage	0.361mA
IP Rating	IP20
Operating Temperature	1° to 40°C (Ambient)
AS2293 Classification	C ₀ =D80 C ₉₀ =D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
1100897	Emergency LED Panel
AUM01370320002 LLIFEM-PRO-SA-CKIT	Emergency Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order