



LLIFEM-PRO-SM-BLK

Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate, Maintained, Clevertest Plus, Black



PRODUCT INFORMATION

Part Number	LLIFEM-PRO-SM-BLK
MIC	UKT00000003201
Description	Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate, Maintained, Clevertest Plus, Black
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO ₄), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	220-240V AC; 50Hz
Total Lumen Output	335lm (Emergency)
Power Consumption	2.4W (Standby) 4.7 (Max)
Inrush Current (Max)	14.0A, 77µs
Earth Leakage	N/A
Rated Emergency Duration	180 minutes
IP Rating	IP20
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)
Operating temperature	0°C to 40°C
Luminaire Classification	X 1 AD 180
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	Battery
8003081	LED Head Assembly
8002958	Driver

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice