LLIFEM-PRO-SM-D2

Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate, Maintained, DALI-2 Emergency



PRODUCT INFORMATION	
Part Number	LLIFEM-PRO-SM-D2
MIC	AUT01110360001
Description	Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate, Maintained, DALI-2 Emergency
Construction	Polycarbonate Enclosure
Mounting	Surface Mount
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Maintained (LEDs permanently ON at 250mA - 182lm) Emergency mode (LEDs running at 550mA - 336lm)
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Factor	0.647
Supply Current	TBA
Power Consumption	6.1W (Lamps ON Max), 3.5W (Lamps ON Standby)
Inrush Current (Peak/Duration)	12.093A
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	1˚C to 40˚C
AS2293 Classification	C0=D80, C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	**DESCRIPTION**
1530231	Battery
8003081	Emergency LED Panel
8003403	Emergency Driver
803062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.