



LLIFEM-PRO-SM-HVG

Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate, Maintained, Zoneworks Hive



PRODUCT INFORMATION

Part Number	LLIFEM-PRO-SM-HVG				
MIC	UKT00000003001				
Description	Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate, Maintained, Zoneworks Hive				
Construction	Polycarbonate Enclosure				
Mounting	Surface Mounted				
Dimensions L x W x H	242mm x 125mm x 48mm				
Weight	0.7kg				
Operating Mode	Maintained				
Testing System	Zoneworks HIVE (RF)				
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)				
Operating Voltage	220-240V AC; 50Hz				
Total Lumen Output	335lm (Emergency)				
Power Consumption	2.7W (Standby) 5.0 (Max)				
Inrush Current (Peak/Duration)	14.0A / 77µs				
Earth Leakage	N/A				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)				
Operating temperature	0°C to 40°C				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>ADF</td><td>180</td></tr></table>	X	1	ADF	180
X	1	ADF	180		
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533231	Battery
8003081	LED Panel
8003840	Emergency Driver
8003330	Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice