



LLIFEM-PRO-SM-HVG

Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate, Maintained, Zoneworks XT Hive



PRODUCT INFORMATION

| | |
|-------------------------------|--|
| Part Number | LLIFEM-PRO-SM-HVG |
| MIC | UKT01810110001 |
| Description | Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate, Maintained, Zoneworks XT Hive |
| Construction | Polycarbonate Enclosure |
| Mounting | Surface Mounted |
| Dimensions L x W x H | 242mm x 125mm x 48mm |
| Weight | 0.7kg |
| Operating Mode | Maintained |
| Testing System | Zoneworks XT HIVE (RF) |
| Battery Type & Manufacturer | Lithium Nanophosphate (LiFePO ₄), Clevertronics |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Lamp(s) | Dual LED (Lifetime warranty on the lamp head and loom assembly) |
| Operating Voltage | 220-240V AC; 50Hz |
| Total Lumen Output | 335lm (Emergency) |
| Power Consumption | 2.7W (Standby) 5.0 (Max) |
| Inrush Current (Max) | 14.0A, 77µs |
| Earth Leakage | N/A |
| Rated Emergency Duration | 180 minutes |
| IP Rating | IP20 |
| Maximum Case Temperature (TC) | 50°C (no heatsink required for lamp control gear) |
| Operating temperature | 0°C to 40°C |
| Luminaire Classification | X 1 ADF 180 |
| Conformity | BS EN 60598-2-22, BS 5266 |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|-------------------|
| 1530231 | Battery |
| 8003081 | LED Head Assembly |
| 8002958 | Driver |
| 8003330 | HIVE Node |

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice