



## LLIFEM-PRO-SMC

### CLEVERTRONICS L10 LIFELIGHT PRO CYLINDER SURFACE MOUNT EMERGENCY



#### PRODUCT INFORMATION

Catalogue Number	LLIFEM-PRO-SMC
MIC	AUT01310490001
Description	L10 Optimum Lifelight PRO, High Performance, Cylinder Surface Mount Emergency Light, Enabled with Clevertest Plus
Construction	Powder coated metal enclosure, PC/ABS head
Mounting	Surface Mount
Dimensions	128mm Diameter, 245mm Height
Weight	1.9kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D80 C <sub>90</sub> =D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

#### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
1100869	LED Head Assembly
LLIFEM-PRO-SMC-CKIT-NP	Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.