



LLIFEM-PRO-SQ

CLEVERTRONICS L10 LIFELIGHT PRO SQUARE



PRODUCT INFORMATION

Part Number	LLIFEM-PRO-SQ
MIC	AUT01310320001
Description	L10 Lithium Nanophosphate LifeLight PRO, high performance, square recessed Maintained Emergency Light, Enabled with Clevertest Plus
Construction	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm x 60mm (Head)
Cut-Out	51mm
Minimum Depth	200mm
Weight	0.8kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	2.4 Watts (Standby), 4.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	Battery
1100847	LED Head Assembly
AUM01370040001 LLIFE-PRO-CKIT	Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.