



## LLIFE

### L10 Lithium Nanophosphate Lifelight, Recessed Emergency Light, Enabled with Clevertest Plus



| PRODUCT INFORMATION           |   |    |     |    |     |
|-------------------------------|---|----|-----|----|-----|
| Part Number                   | LLIFE   |    |     |    |     |
| MIC                           | UKD01310010003  |    |     |    |     |
| Description                   | L10 Lithium Nanophosphate Lifelight, Recessed Emergency Light, Enabled with Clevertest Plus |    |     |    |     |
| Construction                  | PC/ABS Head   |    |     |    |     |
| Mounting                      | Recessed Mount  |    |     |    |     |
| Dimensions                    | 232 x 51mm x 42mm (Control Pack), 95mm Head Diameter (145mm with Adaptor Plate)             |    |     |    |     |
| Ceiling Hole-Cut Out          | 85mm, 135mm (with adaptor plate)  |    |     |    |     |
| Minimum Ceiling Depth         | 120mm, 70mm (with adaptor plate)  |    |     |    |     |
| Weight                        | 0.8kg   |    |     |    |     |
| Operating Mode                | Non-Maintained  |    |     |    |     |
| Testing System                | Clevertest Plus Enabled (Not Activated by Default)  |    |     |    |     |
| Battery                       | Lithium Nanophosphate, 3.3V, 2500mAh  |    |     |    |     |
| Charging Method               | Intelligent Current Limited Constant Voltage  |    |     |    |     |
| Lamp(s)                       | Single white LED (Lifetime warranty on the lamp head and loom assembly)                     |    |     |    |     |
| Operating Voltage             | 240V AC; 50Hz   |    |     |    |     |
| Total Lumen Output            | 188lm (Emergency)   |    |     |    |     |
| Power Consumption             | 1.0 Watts (Standby), 4.2 Watts (Max)  |    |     |    |     |
| Inrush Current (Max)          | 0.3A @ 3668µs   |    |     |    |     |
| Earth Leakage                 | N/A   |    |     |    |     |
| IP Rating                     | IP20  |    |     |    |     |
| Operating Temperature         | 0°C to 40°C   |    |     |    |     |
| Maximum Case Temperature (TC) | 50°C  |    |     |    |     |
| Rated Emergency Duration      | 180 Minutes   |    |     |    |     |
| Compliance Marking            |   |    |     |    |     |
| Luminaire Classification      | <table border="1"><tr><td>X</td><td>0</td><td>AD</td><td>180</td></tr></table>              | X  | 0   | AD | 180 |
| X                             | 0   | AD | 180 |    |     |
| Conformity                    | BS EN 60598-2-22, BS 5266   |    |     |    |     |

| REPLACEMENT PARTS                |             |
|----------------------------------|-------------|
| PART NUMBER                      | DESCRIPTION |
| 1533031                          | Battery     |
| UKM01370040003<br>LLIFE-CKIT-450 | EM Driver   |
| 1100923                          | Lamp Head   |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order