

CLEVERTRONICS L10 OPTIMUM SURFACE MOUNT SWINGBLADE LED EXIT (DALI)



PRODUCT INFORMATION

Part Number	LSBLED-DALI-BLK
MIC	AUA01210940102
Description	LED L10 OPTIMUM Swingblade Exit, 24 metre viewing Distance – Black body
Construction	Metal Frame, White End Caps with Acrylic & Polycarbonate Diffuser
Mounting	Surface Mount, Wall or Ceiling on a slide connect bracket – Single & Double Sided “NOTE: If product is suspended below the ceiling or mounted on a metal surface the Swingblade bracket cover plate accessory (P/N: 2740105) is required to cover the mains terminals.”
Dimensions L x W x H	See Images above
Operating Mode	Maintained
Testing System	DALI Registered
Charging Method	Intelligent current limited constant voltage charger
Diffuser	(All directional inserts included in the box)
Lamp(s)	24 x high intensity, low energy LED, surface mounted onto a replaceable lamp bar - 100,000hour
Operating Voltage	240V
Power Consumption	3.8W (Standby), 5.8W (MAX during 16 hour charge)
IP Rating	IP20
Operating Temperature	1° to 40°C
AS/NZ2293 Classification	C ₀ =D6.3 C ₉₀ =E3.2

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530070	Battery: 3.3Volt, 2.5Ah Li-ion
8002355	PCA: Lithium S/BLADE Driver. #CT10164-L4
8002185	PCA: 24DLED SB LED Strip, #CT10156-D2
8003211	PCA: CT10164-L6 6C83 DALI Reg

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order