




## LUBPRO-BLK

Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, Clevertest Plus, All Pictograms, Single or Double Sided, Black



### PRODUCT INFORMATION

Part Number	LUBPRO-BLK
MIC	UKA00000000601
Description	Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, Clevertest Plus, All Pictograms, Single or Double Sided, Black
Construction	PC/ABS body with PC Diffuser
Mounting	Recessed Ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Ceiling Hole Cut-Out	350mm x 48mm
Minimum Ceiling Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	12 x LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.9 Watts (Standby), 4.1 Watts (Max)
Power Factor	0.38
Supply Current	0.05A
Inrush Current (Peak/Duration)	13A/78µs
Earth Leakage	N/A
Viewing Distance	30m
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Compliance Marking	
Luminaire Classification	X   1   AG   180
Conformity	BS EN 60598-2-22, BS 5266

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533050	Battery
8002952	LED Strip

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order