



LUBPRO-D2-BLK

Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, DALI-2
Emergency, All Pictograms, Single or Double Sided, Black



PRODUCT INFORMATION

Part Number	LUBPRO-D2-BLK			
MIC	UKA01210310001			
Description	Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, DALI-2 Emergency, All Pictograms, Single or Double Sided, Black			
Construction	PC/ABS body with PC Diffuser			
Mounting	Recessed Ceiling			
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)			
Cut-Out	350mm x 48mm			
Minimum Depth	80mm			
Weight	1.1kg			
Operating Mode	Maintained			
Testing System	DALI-2			
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO ₄), Clevertronics			
Charging Method	Intelligent current limited constant voltage			
Diffuser	All directional inserts included in the box			
Lamp(s)	12 x LED, 100,000 hours			
Operating Voltage	240V AC; 50Hz			
Power Consumption	4.1W (Lamps ON Max), 1.9W (Lamps ON Standby)			
Inrush Current (Peak/Duration)	13.08A/84µs			
Earth Leakage	0.331mA			
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating Temperature	0°C to 40°C			
Compliance Marking				
Luminaire Classification	X	1	AFG	180
Applicable Standards	BS EN 60598-2-22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533050	Battery
UKM01270170002	Emergency Driver
8002178	LED Panel
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.