



LUBPRO-D2

Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, DALI-2
Emergency, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	LUBPRO-D2				
MIC	UKA01210290002				
Description	Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, DALI-2 Emergency, All Pictograms, Single or Double Sided				
Construction	PC/ABS body with PC Diffuser				
Mounting	Recessed Ceiling				
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)				
Cut-Out	350mm x 48mm				
Minimum Depth	80mm				
Weight	1.1kg				
Operating Mode	Maintained				
Testing System	DALI-2				
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent current limited constant voltage				
Diffuser	All directional inserts included in the box				
Lamp(s)	12 x LED, 100,000 hours				
Operating Voltage	240V AC; 50Hz				
Power Consumption	4.1W (Lamps ON Max), 1.9W (Lamps ON Standby)				
Inrush Current (Peak/Duration)	13.08A/84µs				
Earth Leakage	0.331mA				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating Temperature	0°C to 40°C				
Luminaire Classification	X	1	AFG	180	
Applicable Standards	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533050	Battery
UKM01270170002 LUBPRO-CKIT-D2-70	Emergency Driver
8002178	LED Strip
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.