



LUBPRO-DALI

CLEVERTRONICS L10 ULTRABLADE PRO



PRODUCT INFORMATION	
Part Number	LUBPRO-DALI
MIC	UKA01210030002
Description	L10 Lithium Nanophosphate Ultrablade Pro
Construction	PC/ABS body with PC Diffuser
Mounting	Wall, Ceiling single-Sided & Ceiling Double-Sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.1kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	12 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	4.1W (Lamps ON Max), 1.9W (Lamps ON Standby)
IP Rating	IP20
Operating Temperature	0°C to 40°C
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

PRODUCT INFORMATION					
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>AFG</td><td>180</td></tr></table>	X	1	AFG	180
X	1	AFG	180		



LUBPRO-DALI

CLEVERTRONICS L10 ULTRABLADE PRO

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	Battery
UKM01270010002 LUBPRO-CKIT-DALI-70	Emergency Driver
8002178	LED Strip
8003060	Dali Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.