LUBPRO-HVG-BLK

Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, Zoneworks HIVE, All Pictograms, Single or Double Sided, Black

PRODUCT INFORMATION	
Part Number	LUBPRO-HVG-BLK
MIC	AUA01910200001
Description	Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, Zoneworks HIVE, All Pictograms, Single or Double Sided, Black
Construction	PC/ABS body with PC diffuser
Mounting	Recessed Ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Weight	1.1kg
Operating Mode	Maintained, supports 4-Hour Emergency Duration
Testing System	Zoneworks HIVE (RF) 2.4GHz
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Supply Current	0.033A
Power Factor	0.36
Power Consumption	2.8 Watts (Standby), 4.2 Watts (Max)
Inrush Current (Peak/Duration)	TBC
Earth Leakage	TBC
IP Rating	IP20
Operating Temperature	1˚C to 40˚C
AS2293 Classification	C0=E6.3 C90=E6.3
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	Class II double insulated

REPLACEMENT PARTS	
PART NUMBER	**DESCRIPTION**
1530050	Battery
8002178	LED Panel
AUM01970110001	Emergency Driver
8003560	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.