



## LUBPRO-HVG-BLK

Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, Zoneworks XT Hive, All Pictograms, Single or Double Sided, Black



PRODUCT INFORMATION	
Part Number	LUBPRO-HVG-BLK
MIC	UKA00000000801
Description	Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, Zoneworks XT Hive, All Pictograms, Single or Double Sided, Black
Construction	PC/ABS body with PC Diffuser
Mounting	Recessed Ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Ceiling Hole Cut-Out	350mm x 48mm
Minimum Ceiling Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	12 x LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.9 Watts (Standby), 4.1 Watts (Max)
Viewing Distance	30m
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li></ul> Battery short-circuit protection (charging will resume upon removal of fault)
Luminaire Classification	X   1   AGF   180

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,no Brkt
8002178	PCA:UBP LED strip PCB Assy (CT10602-Dx)
UKM01870020001	LUBPRO-CKIT-HVG-70, Ultrablade Pro, Control Only, L10, HVG, 70mA
8003330	PCA: 2.4Ghz RF Node CT10748-A1 Int Antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order