LUBPRO-HVG-BLK

Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, Zoneworks Hive, All Pictograms, Single or Double Sided, Black



PRODUCT INFORMATION	
Part Number	LUBPRO-HVG-BLK
MIC	UKA00000000802
Description	Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, Zoneworks Hive, All Pictograms, Single or Double Sided, Black
Construction	PC/ABS body with PC Diffuser
Mounting	Recessed Ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Ceiling Hole Cut-Out	350mm x 48mm
Minimum Ceiling Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Zoneworks Hive (RF) 2.4GHz
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	12 x LED, 100,000 hours
Operating Voltage	220-240V~50Hz
Power Factor	0.446
Supply Current	0.038A
Power Consumption	1.9 Watts (Standby), 4.1 Watts (Max)
Inrush Current (Peak/Duration)	13.08A / 84µs
Earth Leakage	0.331mA
Viewing Distance	30m
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0˚C to 40˚C
Luminaire Classification	X | 1 | AFG | 180
Compliance Marking	UKCA CE
Appliance Class	☐ Class II double insulated
Conformity	BS EN 60598-2-22, BS 5266

LUBPRO-HVG-BLK

Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, Zoneworks Hive, All Pictograms, Single or Double Sided, Black

REPLACEMENT PARTS	
PART NUMBER	**DESCRIPTION**
1533050	Battery
8002178	LED Panel
UKM01870020002	Emergency Driver
8003330	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order