

Ultrablade Pro Exit, Recessed Wall Mount, Vertical, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	LUBPRO-HVG-V
MIC	AUA01910210001
Description	Ultrablade Pro Exit, Recessed Wall Mount, Vertical, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, All Pictograms, Single or Double Sided
Construction	PC/ABS body with PC diffuser
Mounting	Recessed Wall Mount, Single or Double Sided
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Zoneworks XT HVIE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Vertical legend , 1 box solution
Lamp(s)	12 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =6.3 C ₉₀ =6.3
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
8003130	PCA:CUBPRO Driver #CT10142-L9 DALI Gen 2
AUM01370010001	Ultrablade Pro, Control Only, CT10142-L9, L10
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order