

CLEVERTRONICS L10 ULTRABLADE PRO (ZONWORKS HIVE)



PRODUCT INFORMATION

Catalogue Number	LUBPRO-HVG
MIC	UKA01810040001
Description	L10 Lithium Nanophosphate Ultrablade Pro Blade Exit
Construction	PC/ABS body with PC Diffuser
Mounting	Recessed Ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Ceiling Hole Cut-Out	350mm x 48mm
Minimum Ceiling Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO ₄), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	12 x LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.9 Watts (Standby), 4.1 Watts (Max)

PRODUCT INFORMATION

Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) 			
Luminaire Classification	X	1	AGF	180

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,no Brkt
8002178	PCA:UBP LED strip PCB Assy (CT10602-Dx)
UKM01870020001	LUBPRO-CKIT-HVG-70, Ultrablade Pro, Control Only, L10, HVG, 70mA
8003250	PCA: UK RF Node CT10720-A1 Ext Antenna

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.