



# LUBPRO-RS-HVG

CLEVERTRONICS L10 ULTRABLADE PRO BLADE EXIT ROD SUSPENDED  
(ZONWORKS HIVE)



PRODUCT INFORMATION	
Part Number	LUBPRO-RS-HVG
MIC	UKA01810120001
Description	L10 Lithium Nanophosphate Ultrablade Pro Blade Exit, Rod suspended
Construction	PC/ABS body with PC Diffuser
Mounting	Recessed Ceiling - Rod suspended
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly)
Ceiling Hole Cut-Out	350mm x 48mm
Minimum Ceiling Depth	80mm
Weight	1.5kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	12 x LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.9 Watts (Standby), 4.1 Watts (Max)
Viewing Distance	30m
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li><li>• Battery short-circuit protection (charging will resume upon removal of fault)</li><li>• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts</li></ul>
Luminaire Classification	X   1   AFG   180
Conformity	BS EN 60598-2-22, BS 5266

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice



# LUBPRO-RS-HVG

CLEVERTRONICS L10 ULTRABLADE PRO BLADE EXIT ROD SUSPENDED  
(ZONWORKS HIVE)

## REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	Battery
8011493	LED Strip
UKM01870020001 LUBPRO-CKIT-HVG-70	EM Driver
8003330	RF Node HVG

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice