



LUBPRO-RS-HVG

Ultrablade Pro Exit, Recessed Ceiling Mount, Rod Suspended, L10 Nanophosphate, Zoneworks Hive, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	LUBPRO-RS-HVG				
MIC	UKA01810120002				
Description	Ultrablade Pro Exit, Recessed Ceiling Mount, Rod Suspended, L10 Nanophosphate, Zoneworks Hive, All Pictograms, Single or Double Sided				
Construction	PC/ABS body with PC Diffuser				
Mounting	Recessed Ceiling - Rod suspended				
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly)				
Ceiling Hole Cut-Out	350mm x 48mm				
Minimum Ceiling Depth	80mm				
Weight	1.5kg				
Operating Mode	Maintained				
Testing System	Zoneworks HIVE (RF) 2.4GHz				
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	All directional inserts included in the box				
Lamp(s)	12 x LED, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	1.9 Watts (Standby), 4.1 Watts (Max)				
Earth Leakage	0.395				
IP Rating	IP20				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Luminaire Classification	X	1	AFG	180	
Conformity	BS EN 60598-2-22, BS 5266				
Compliance Marking					

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice



LUBPRO-RS-HVG

Ultrablade Pro Exit, Recessed Ceiling Mount, Rod Suspended, L10
Nanophosphate, Zoneworks Hive, All Pictograms, Single or Double Sided

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533050	Battery
8011493	LED Panel
UKM01870020002	Emergency Driver
8003330	Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice