



LUBPRO-RS-TH-D2-DS-RAOW

Ultrablade Pro Exit , Surface Mount, Rod Suspended, L10
Nanophosphate, DALI-2 Emergency, Theatre Version, Running Man
Arrow One Way, Double Sided



PRODUCT INFORMATION

Part Number	LUBPRO-RS-TH-D2-DS-RAOW
MIC	AUA00000022601
Description	Ultrablade Pro Exit , Surface Mount, Rod Suspended, L10 Nanophosphate, DALI-2 Emergency, Theatre Version, Running Man Arrow One Way, Double Sided
Construction	PC/ABS body with PC Diffuser
Mounting	Recessed Ceiling - Rod suspended Blade suspended with 5mm diameter; steel rods secured by 2 x “grub-screw” at each end of the rod. Rod suspension system supplies power to the LED lamp bar mounted on top of blade. Note: Steel Rods supplied with fitting assembly, 1500mm long.
Dimensions L x W x H	Blade Assembly: 317mm x 8.7mm x 157mm Ceiling Mount Control Gear Enclosure: 347mm x 48mm x 65mm Ceiling Mount Cover Plate: 385mm x 67mm
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Weight	1.5kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Version, Running Man Arrow One Way, Double Sided
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4W (Standby), 3.7W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	Battery
8011493	LED Panel
AUM01370470001 LUBPRO-CKIT-20	Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order