



LUBPRO-RS-TH-RD

Ultrablade Pro Exit, Recessed Ceiling Mount, Rod Suspended, L10
Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow
Down, Single Sided



PRODUCT INFORMATION

Part Number	LUBPRO-RS-TH-RD			
MIC	UKA00000037401			
Description	Ultrablade Pro Exit, Recessed Ceiling Mount, Rod Suspended, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow Down, Single Sided			
Construction	PC/ABS body with PC Diffuser			
Mounting	Recessed Ceiling - Rod suspended			
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly)			
Ceiling Hole Cut-Out	350mm x 48mm			
Minimum Ceiling Depth	80mm			
Weight	1.5kg			
Operating Mode	Maintained			
Testing System	Clevertest Plus Enabled (Not activated by default)			
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Diffuser	Theatre Mask, Running Man Arrow Down, Single Sided			
Lamp(s)	12 x LED, 100,000 hours			
Operating Voltage	220-240V AC; 50Hz			
Power Factor	0.38			
Supply Current	0.044A			
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)			
Power Factor	0.38			
Earth Leakage	0.331mA			
Inrush Current (Peak/Duration)	13.08A/84µs			
IP Rating	IP20			
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Luminaire Classification	X	1	AG	180
Conformity	BS EN 60598-2-22, BS 5266			
Compliance Marking	UK CE			

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice



LUBPRO-RS-TH-RD

Ultrablade Pro Exit, Recessed Ceiling Mount, Rod Suspended, L10
Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow
Down, Single Sided

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533030	Battery
8002178	LED Panel
800-00035	Emergency Driver

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice