



LUBPRO-RS

L10 Optimum Ultrablade Pro Blade Exit, Rod Suspended,
Enabled with Clevertest Plus



PRODUCT INFORMATION	
Part Number	LUBPRO-RS
MIC	AUA01310550003
Description	L10 Optimum Ultrablade Pro Blade Exit, Rod Suspended, Enabled with Clevertest Plus
Construction	PC/ABS body with PC Diffuser
Mounting	Recessed Ceiling - Rod Suspended Blade Suspended with 5mm diameter; steel rods secured by 2 x “grub-screw” at each end of the rod. Rod suspension system supplies power to the LED lamp bar mounted on top of blade. Note: Steel Rods supplied with fitting assembly, 1500mm Long
Dimensions L x W x H	Blade Assembly: 317mm x 8.7mm x 157mm Ceiling Mount Control Gear Enclosure: 347mm x 48mm x 65mm Ceiling Mount Cover Plate: 385mm x 67mm
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Weight	1.5kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	All Directional Inserts Included
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.5W (Standby), 3.9W (Max)
Inrush Current (Peak/Duration)	15.5A/150µS
Earth Leakage	0.369mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E5 C90=E5
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	



LUBPRO-RS

L10 Optimum Ultrablade Pro Blade Exit, Rod Suspended,
Enabled with Clevertest Plus

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	Battery
8011493	Emergency LED Panel
AUM01370010002 LUBPRO-CKIT	Emergency Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order