



LUBPRO-SM-BLK

Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus,
All Pictograms, Single or Double Sided, Black



PRODUCT INFORMATION

Part Number	LUBPRO-SM-BLK				
MIC	UKA01310260001				
Description	Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, All Pictograms, Single or Double Sided, Black				
Construction	PC/ABS body with PC diffuser				
Mounting	Surface Mount				
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)				
Weight	1.0kg				
Operating Mode	Maintained				
Testing System	Clevertest Plus Enabled (Not activated by default)				
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent current limited constant voltage				
Diffuser	All pictograph directional inserts included in the box				
Lamp(s)	12 x Duris E3 LED, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	1.9 Watts (Standby), 4.1 Watts (Max)				
Inrush Current (Max)	13A@78µs				
Earth Leakage	N/A				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating Temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">Battery overvoltage & overcurrent protectionBattery deep discharge protectionSupply voltage polarity reversal protectionBattery short-circuit protection (charging will resume upon removal of fault)				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>AG</td><td>180</td></tr></table>	X	1	AG	180
X	1	AG	180		
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	Battery
8002178	Emergency LED Panel
8002951	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.