




LUBPRO-SM-D2-V-BLK

Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, DALI-2
Emergency, All Pictograms, Single or Double Sided, Black



PRODUCT INFORMATION

| | |
|--------------------------|--|
| Part Number | LUBPRO-SM-DALI-V-BLK |
| MIC | AUA01211740001 |
| Description | Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, All Pictograms, Single or Double Sided, Black |
| Construction | ABS Frame with Acrylic & PC Diffuser |
| Mounting | Wall, ceiling single-sided & ceiling double-sided |
| Dimensions L x W x H | 317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base) |
| Weight | 1.0kg |
| Operating Mode | Maintained |
| Testing System | DALI-2 |
| Battery | Lithium Nanophosphate, 3.3V 2500mAh |
| Charging Method | Intelligent current limited constant voltage |
| Diffuser | All pictograph directional inserts included in the box |
| Lamp(s) | 12 x Duris E3 LED, 100,000 hours |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 1.7 Watts (Standby), 4.0 Watts (Max) |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C0=E1.25, C90=B1.25 |
| Viewing Distance | 24m |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) |  |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|-------------|
| 1530030 | Battery |
| 8002178 | LED Strip |
| 8003135 | Driver |
| 8003062 | DALI-2 Node |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order