




## LUBPRO-SM-D2

L10 Lithium Nanophosphate Ultrablade  
Pro Surface Mount Blade Exit, DALI-2



### PRODUCT INFORMATION

|                                |   |   |     |     |
|--------------------------------|---|---|-----|-----|
| Part Number                    | LUBPRO-SM-D2  |   |     |     |
| MIC                            | UKA01210300001  |   |     |     |
| Description                    | L10 Lithium Nanophosphate Ultrablade Pro Surface Mount Blade Exit, DALI-2           |   |     |     |
| Construction                   | PC/ABS body with PC Diffuser  |   |     |     |
| Mounting                       | Wall, Ceiling single-Sided & Ceiling Double-Sided                                   |   |     |     |
| Dimensions L x W x H           | 317mm x 8.7mm x 157mm (Blade Assembly)<br>360mm x 47mm x 72mm (Base)                |   |     |     |
| Weight                         | 1.1kg   |   |     |     |
| Operating Mode                 | Maintained  |   |     |     |
| Testing System                 | DALI-2  |   |     |     |
| Battery Type and Manufacturer  | Lithium Nanophosphate (LiFePO4), Clevertronics                                      |   |     |     |
| Charging Method                | Intelligent Current Limited Constant Voltage  |   |     |     |
| Diffuser                       | All directional inserts included in the box   |   |     |     |
| Lamp(s)                        | 12 x LED, 100,000 hours   |   |     |     |
| Operating Voltage              | 220-240V AC; 50Hz   |   |     |     |
| Power Factor                   | 0.38  |   |     |     |
| Supply Current                 | 0.05A   |   |     |     |
| Power Consumption              | 1.9W (Standby), 4.1W (Max)  |   |     |     |
| Inrush Current (Peak/Duration) | 18.9A / 138µs   |   |     |     |
| Earth Leakage                  | N/A   |   |     |     |
| Viewing Distance               | 30m   |   |     |     |
| IP Rating                      | IP20  |   |     |     |
| Rated Emergency Duration       | 180 minutes   |   |     |     |
| Operating temperature          | 0°C to 40°C   |   |     |     |
| Compliance Marking             |  |   |     |     |
| Luminaire Classification       | X   | 1 | AFG | 180 |
| Conformity                     | BS EN 60598-2-22, BS 5266   |   |     |     |

### REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION      |
|-------------|------------------|
| 1533030     | Battery          |
| 8003837     | Emergency Driver |
| 8002178     | LED Panel        |
| 8003062     | Node             |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.