

LUBPRO-SM-DALI-BLK

CLEVERTRONICS L10 ULTRABLADE PRO SURFACE MOUNT BLADE EXIT – BLACK (DALI)



PRODUCT INFORMATION	V
Part Number	LUBPRO-SM-DALI-BLK
MIC	UKA01210070002
Description	L10 Optimum Ultrablade Pro Surface Mount Blade Exit, Black
Construction	PC/ABS body with PC Diffuser
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.1kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	12 x LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.9 Watts (Standby), 4.1 Watts (Max)
Viewing Distance	30m
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Protection	 Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts
Luminaire Classification	X 1 AFG 180
Conformity	BS EN 60598-2-22, BS 5266

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice





LUBPRO-SM-DALI-BLK

CLEVERTRONICS L10 ULTRABLADE PRO SURFACE MOUNT BLADE EXIT – BLACK (DALI)

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead, no Brkt
8002178	PCA:UBP LED strip PCB Assy (CT10602-Dx)
8002951	PCA: LUBPRO-SM #CT10142-L9 6C70 CTP UK OWC
8003060	PCA: New DALI #CT10629-Ax

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice

