

CLEVERTRONICS L10 ULTRABLADE PRO SURFACE MOUNT (DALI)



PRODUCT INFORMATION

Catalogue Number	LUBPRO-SM-DALI
MIC	UKA01210040002
Description	L10 Lithium Nanophosphate Ultrablade Pro Surface Mount Blade Exit
Construction	PC/ABS body with PC Diffuser
Mounting	Wall, Ceiling single-Sided & Ceiling Double-Sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.1kg
Operating Mode	Maintained
Testing System	DALI Registered
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	12 x LED, 100,000 hours
Power Consumption	1.9 Watts (Standby), 4.1 Watts (Max)

PRODUCT INFORMATION

Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) 			
Luminaire Classification	X	1	AGF	180

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead,noBrkt
8002178	PCA:UBP LED strip PCB Assy (CT10602-Dx)
8002951	PCA: LUBPRO-SM #CT10142-L9 6C70 UK OWC
8003060	PCA: New DALI #CT10629-Ax

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.