



## LUBPRO-SM-HVG-BLK

Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, All Pictograms, Single or Double Sided, Black



PRODUCT INFORMATION				
Part Number	LUBPRO-SM-HVG-BLK			
MIC	UKA01810410001			
Description	Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, All Pictograms, Single or Double Sided, Black			
Construction	PC/ABS body with PC Diffuser			
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided			
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)			
Weight	1.1kg			
Operating Mode	Maintained			
Testing System	Zoneworks XT HIVE (RF)			
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Diffuser	All directional inserts included in the box			
Lamp(s)	12 x LED, 100,000 hours			
Operating Voltage	220-240V AC; 50Hz			
Power Consumption	1.9 Watts (Standby), 4.1 Watts (Max)			
Inrush Current (Max)	13.08A, 84µs			
Earth Leakage	13.8mA			
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> <li>• Battery overvoltage &amp; overcurrent protection</li> <li>• Battery deep discharge protection</li> <li>• Supply voltage polarity reversal protection</li> <li>• Battery short-circuit protection (charging will resume upon removal of fault)</li> <li>• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts</li> </ul>			
Luminaire Classification	X	1	AFG	180
Conformity	BS EN 60598-2-22, BS 5266			

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice



## LUBPRO-SM-HVG-BLK

Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT  
Hive, All Pictograms, Single or Double Sided, Black

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	Battery
8002178	LED Strip
8002951	Driver
8003330	HVG Node

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice