LUBPRO-SM-HVG-V-BLK

Ultrablade Pro Exit, Surface Mount, Vertical, L10 Nanophosphate, Zoneworks Hive, All Pictograms, Single or Double Sided, Black



PRODUCT INFORMATION	
Part Number	LUBPRO-SM-HVG-V-BLK
MIC	AUA01910270001
Description	Ultrablade Pro Exit, Surface Mount, Vertical, L10 Nanophosphate, Zoneworks Hive, All Pictograms, Single or Double Sided, Black
Construction	PC/ABS Body with PC Diffuser
Mounting	Wall Mount single & double-sided
Dimensions L x W x H	157mm x 8.7mm x 317mm (Blade Assembly) 72mm x 47mm x 360mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	Zoneworks HIVE (RF) 2.4GHz
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	All vertical pictograph directional inserts included in the box
Lamp (s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Factor	0.38
Supply Current	0.0434A
Power Consumption	1.7 Watts (Standby), 4.0 Watts (Max)
Inrush Current (Peak/Duration)	14.7A/66µs
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	1˚C to 40˚C
AS2293 Classification	C_0=E1.25 C_{90}=B1.25
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	Class II double insulated

LUBPRO-SM-HVG-V-BLK

Ultrablade Pro Exit, Surface Mount, Vertical, L10 Nanophosphate, Zoneworks Hive, All Pictograms, Single or Double Sided, Black

REPLACEMENT PARTS	
PART NUMBER	**DESCRIPTION**
1530030	Battery
8002178	LED Panel
8003503	Emergency Driver
8003560	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order