

## **LUBPRO-SM-HVG** CLEVERTRONICS L10 ULTRABLADE PRO BLADE EXIT SURFACE MOUNT (ZONEWORKS XT HIVE)



PRODUCT INFORMATION						
Part Number	LUBPRO-SM-HVG					
MIC	UKA01810020002					
Description	L10 Optimum Ultrablade Pro Surface Mount Blade Exit					
Construction	PC/ABS body with PC Diffuser					
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided					
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)					
Weight	1.1kg					
Operating Mode	Maintained					
Testing System	Zoneworks XT HIVE (RF)					
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics					
Charging Method	Intelligent Current Limited Constant Voltage					
Diffuser	All directional inserts included in the box					
Lamp(s)	12 x LED, 100,000 hours					
Operating Voltage	220-240V AC; 50Hz					
Power Consumption	1.9 Watts (Standby), 4.4 Watts (Max)					
Viewing Distance	30m					
Rated Emergency Duration	180 minutes					
IP Rating	IP20					
Operating temperature	0°C to 40°C					
Protection	<ul> <li>Battery overvoltage &amp; overcurrent protection</li> <li>Battery deep discharge protection</li> <li>Supply voltage polarity reversal protection</li> <li>Battery short-circuit protection (charging will resume upon removal of fault)</li> <li>Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts</li> </ul>					
Luminaire Classification	Х	1	AFG	180		
Conformity	BS EN 60598-2-22, BS 5266					

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice





## LUBPRO-SM-HVG

**LUBPRO-SM-HVG** CLEVERTRONICS L10 ULTRABLADE PRO BLADE EXIT SURFACE MOUNT (ZONEWORKS XT HIVE) (ZONEWORKS XT HIVE)

REPLACEMENT PARTS			
PART NUMBER	DESCRIPTION		
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead, no Brkt		
8002178	PCA:UBP LED strip PCB Assy (CT10602-Dx)		
8002951	PCA: LUBPRO-SM #CT10142-L9 6C70 CTP UK OWC		
8003330	PCA: 2.4Ghz RF Node CT10748-A1 Int Antenna		

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice

