



LUBPRO-SM-HVG

L10 Optimum Ultrablade Pro Surface Mount Blade Exit



PRODUCT INFORMATION

Part Number	LUBPRO-SM-HVG			
MIC	UKA01810020003			
Description	L10 Optimum Ultrablade Pro Surface Mount Blade Exit			
Construction	PC/ABS body with PC Diffuser			
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided			
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)			
Weight	1.35kg			
Operating Mode	Maintained			
Testing System	Zoneworks XT HIVE (RF)			
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Diffuser	All directional inserts included in the box			
Lamp(s)	12 x LED, 100,000 hours			
Operating Voltage	220-240V AC; 50Hz			
Power Consumption	1.9 Watts (Standby), 4.4 Watts (Max)			
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Luminaire Classification	X	1	AFG	180
Conformity	BS EN 60598-2-22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533030	Battery
8002178	LED strip
8003837	EM Driver
8003330	Hive Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice