




LUBPRO-SM-RS-D2-BLK

Ultrablade Pro Exit, Surface Mount, Rod Suspended, L10 Nanophosphate, DALI-2 Emergency, All Pictograms, Single or Double Sided, Black



PRODUCT INFORMATION	
Part Number	LUBPRO-SM-RS-D2-BLK
MIC	AUA00000032501
Description	Ultrablade Pro Exit, Surface Mount, Rod Suspended, L10 Nanophosphate, DALI-2 Emergency, All Pictograms, Single or Double Sided, Black
Construction	PC/ABS body with PC Diffuser, Stainless Steel Rods
Mounting	Surface Mount Ceiling - Rod suspended - Blade suspended with unpainted stainless-steel rods, secured by 2 x "grub- screws" at each end of the rod - Rod suspension system supplies power to the LED lamp bar mounted on top of blade. Steel Rods supplied with fitting assembly.
Dimensions L x W x H	Blade Assembly: 317mm x 8.7mm x 157mm Ceiling Mount Control Gear Enclosure: 360mm x 47mm x 72mm Rods: 1500mm x 5mm
Weight	1.5kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	All Directional Inserts Included
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Supply Current	0.05A
Power Factor	0.38
Power Consumption	1.4W (Standby), 3.7W (Max)
Inrush Current (Peak/Duration)	TBC
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E6.3 C90=E6.3
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	☐ Class II double insulated



LUBPRO-SM-RS-D2-BLK

Ultrablade Pro Exit, Surface Mount, Rod Suspended, L10
Nanophosphate, DALI-2 Emergency, All Pictograms,
Single or Double Sided, Black

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	Battery
8003135	Emergency Driver
8011493	LED Strip
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order