



LUBPRO-SM-RS-HVG-BLK

Clevertronics L10 Ultrablade Pro Blade Exit
Surface Mounted, Rod Suspended, Black



PRODUCT INFORMATION	
Part Number	LUBPRO-SM-RS-HVG-BLK
MIC	AUA01910180001
Description	Clevertronics L10 Ultrablade Pro Blade Exit, Surface Mounted, Rod Suspended, Black
Construction	PC/ABS body with PC Diffuser, Stainless Steel Rods
Mounting	Surface Mount Ceiling - Rod suspended - Blade suspended with unpainted stainless-steel rods, secured by 2 x “grub- screws” at each end of the rod - Rod suspension system supplies power to the LED lamp bar mounted on top of blade. Steel Rods supplied with fitting assembly.
Dimensions L x W x H	Blade Assembly: 317mm x 8.7mm x 157mm Ceiling Mount Control Gear Enclosure: 360mm x 47mm x 72mm Rods: 1500mm x 5mm
Weight	1.5kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF) 2.4GHz
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	All Directional Inserts Included
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4W (Standby), 3.7W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E5 C90=E5
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	



LUBPRO-SM-RS-HVG-BLK

Clevertronics L10 Ultrablade Pro Blade Exit
Surface Mounted, Rod Suspended, Black

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	Battery
8003135	Emergency Driver
8011493	LED Strip
8003560	Hive Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order