LUBPRO-SM-RS-TH-DS-RAOW

Ultrablade Pro Exit, Surface Mount, Rod Suspended, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow One Way, Double Sided



PRODUCT INFORMATION	
Part Number	LUBPRO-SM-RS-TH-DS-RAOW
MIC	AUA00000052501
Description	Ultrablade Pro Exit, Surface Mount, Rod Suspended, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow One Way, Double Sided
Construction	PC/ABS body with PC Diffuser
Mounting	Surface Mount Ceiling - Rod suspended Blade suspended with 5mm diameter; steel rods secured by 2 x “grub-screw” at each end of the rod. Rod suspension system supplies power to the LED lamp bar mounted on top of blade. Note: Steel Rods supplied with fitting assembly, 1500m long.
Dimensions L x W x H	Blade Assembly: 317mm x 8.7mm x 157mm Ceiling Mount Control Gear Enclosure: 360mm x 47mm x 72mm Rods: 1500mm x 5mm
Weight	1.5kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Version, Double Sided, Running Man Arrow One Way
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1˚C to 40˚C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	**DESCRIPTION**
1530030	Battery
8003503	Emergency LED Panel
AUM01370470001	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order