



## LUBPRO-SM-TH-D2-DS-R

Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, DALI-2  
Emergency, Theatre Version, Running Man, Double Sided



PRODUCT INFORMATION	
Part Number	LUBPRO-SM-TH-D2-DS-R
MIC	AUA00000037201
Description	Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, Theatre Version, Running Man, Double Sided
Construction	PC/ABS Body with PC Diffuser
Mounting	Wall or Ceiling Mounted, Double sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Version, Running Man, Double Sided
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Supply Current	0.034A
Power Factor	0.31
Power Consumption	1.7W (Standby), 4.0W (Max)
Inrush Current (Peak/Duration)	12.934A/87µs
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	<input type="checkbox"/> Class II double insulated

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530030	Battery
8002178	LED Panel
8003173	Emergency Driver
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order