



LUBPRO-SM-TH-D2-R

Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, DALI-2
Emergency, Theatre Version, Running Man, Single Sided



PRODUCT INFORMATION

Part Number	LUBPRO-SM-TH-D2-R
MIC	AUA00000013701
Description	Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, Theatre Version, Running Man, Single Sided
Construction	PC/ABS Body with PC Diffuser
Mounting	Wall or Ceiling Mounted, Single Sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Version, Running Man, Single Sided
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.7W (Standby), 4.0W (Max)
Inrush Current(Peak/Duration)	12.493A
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	Battery
8002178	LED Strip
8003503	Driver
8003062	Emergency Node – DALI-2

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order