LUBPRO-SM-TH-HVG-RU

Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, Theatre Version, Running Man Arrow Up, Single Sided

PRODUCT INFORMATION	
Part Number	LUBPRO-SM-HVG-RU
MIC	UKA01860060001
Description	Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, Theatre Version, Running Man Arrow UP, Single Sided
Construction	PC/ABS body with PC Diffuser
Mounting	Wall, Ceiling single-Sided & Ceiling Double-Sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	Zoneworks XT Hive
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre mask, Running man with Up Arrow
Lamp(s)	12 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.8W (Standby), 3.9W (Max)
Inrush Current (Max)	13.08A@84µs
Earth Leakage	0.331mA
IP Rating	IP20
IK Rating	N/A
Operating Temperature	0˚C to 40˚C
Viewing Distance	30m

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0˚C to 40˚C
Protection	• Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault)
Luminaire Classification	X 1 AFG 180

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	Battery
8003168	Emergency Driver
8002178	LED Strip
8003330	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order