



## LUBPRO-SM-TH-HVG-R

Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Theatre Version, Running Man, Single Sided



### PRODUCT INFORMATION

Part Number	LUBPRO-SM-TH-HVG-R
MIC	AUA01960020001
Description	Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Theatre Version, Running Man, Single Sided
Construction	PC/ABS Body with PC Diffuser
Mounting	Wall or Ceiling Mounted, Single-Sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate 3.3V 2.5Ah
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre Mask, Single Sided, Running Man (Must specify diffuser combination)
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead, no Brkt
8002178	PCA:UBP LED strip PCB Assy (CT10602-Dx)
8003135	PCA:CUBPRO-SM Driver CT10142-L9 DALI Reg,CTP,HV,ZW
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order