




## LUBPRO-SM-TH-RU

Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate,  
Theatre Version, Running Man Arrow Up, Single Sided



### PRODUCT INFORMATION

Part Number	LUBPRO-SM-TH-RU
MIC	UKA00000004901
Description	Ultrablade Pro Exit, Surface Mount, L10 Nanophosphate, Theatre Version, Running Man Arrow UP, Single Sided
Material	PC/ABS body with PC Diffuser
Mounting	Wall, Ceiling single-Sided
Dimensions	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	Manual Testing
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Driver	Theatre mask, Running man with Up Arrow
Lamp(s)	12 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Factor	0.38
Supply Current	0.044A
Power Consumption	1.4W (Standby), 3.7W (Max)
Inrush Current (Peak/Duration)	13.08A/84µs
Earth Leakage	0.331mA
IP Rating	IP20
Operating Temperature	0°C to 40°C
Viewing Distance	30m
Rated Emergency Duration	180 minutes
Compliance Marking	
Luminaire Classification	X   1   AFG   180
Conformity	BS EN 60598-2-22, BS 5266

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533030	Battery
800-00035	Emergency Driver
8002178	Emergency LED Panel

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order