

CLEVERTRONICS L10 ULTRABLADE PRO SURFACE MOUNT



PRODUCT INFORMATION

Catalogue Number	LUBPRO-SM
MIC	UKA01310040002
Description	L10 Lithium Nanophosphate Ultrablade Pro Surface Mount Blade Exit with Clevertest Plus Enabled
Construction	PC/ABS body with PC Diffuser
Mounting	Wall, Ceiling single-Sided & Ceiling Double-Sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.1kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	12 x LED, 100,000 hours
Power Consumption	1.9 Watts (Standby), 4.1 Watts (Max)

PRODUCT INFORMATION

Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) 			
Luminaire Classification	X	1	AG	180

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead,noBrkt
8002178	PCA:UBP LED strip PCB Assy (CT10602-Dx)
8002951	PCA: LUBPRO-SM #CT10142-L9 6C70 CTP UK OWC

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.