



LUBPRO-SM

L10 Optimum Ultrablade Pro Surface Mount Blade Exit



PRODUCT INFORMATION

Part Number	LUBPRO-SM				
MIC	UKA01310040003				
Description	L10 Optimum Ultrablade Pro Surface Mount Blade Exit				
Construction	PC/ABS body with PC Diffuser				
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided				
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)				
Weight	1.35kg				
Operating Mode	Maintained				
Testing System	Clevertest Plus Enabled (Not activated by default)				
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	All directional inserts included in the box				
Lamp(s)	12 x LED, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Supply Current	0.05A				
Power Factor	0.38				
Power Consumption	1.6 Watts (Standby), 3.8 Watts (Max)				
Inrush Current (Peak/Duration)	18.9A/138µs				
Earth Leakage	N/A				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Luminaire Classification	X	1	AG	180	
Conformity	BS EN 60598-2-22, BS 5266				
Compliance Marking					

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533030	Battery
8002178	LED Panel
8003837	Emergency Driver

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice