



## LUBPRO-TH-D2-R

Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, DALI-2  
Emergency, Theatre Version, Running Man, Single Sided



### PRODUCT INFORMATION

Part Number	LUBPRO-TH-D2-R
MIC	AUA00000013801
Description	Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, DALI-2 Emergency, Theatre Version, Running Man, Single Sided
Construction	ABS frame with acrylic & PC diffuser
Mounting	Recessed ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly)
Cut-Out	385mm x 67mm (Cover Plate)
Minimum Ceiling Depth	350mm x 48mm
Weight	80mm
Operating Mode	Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man (Must specify diffuser combination)
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8W (Standby), 4.2W (Max)
Inrush Current (Peak/Duration)	3.08A/84µs
Earth Leakage	0.331mA
IP Rating	IP20
IK Rating	N/A
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	Battery
8002178	LED Strip
AUM00000001401 LUBPRO-CKIT-D2	Driver Pack
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.