



## LUBPRO-TH-DALI-RL

CLEVERTRONICS L10 ULTRABLADE PRO, THEATRE (DALI)



### PRODUCT INFORMATION

Part Number	LUBPRO-TH-DALI-RL
MIC	AUA01260790002
Description	L10 Lithium Nanophosphate Ultrablade Pro blade Exit, Theatre
Construction	ABS frame with acrylic & PC diffuser
Mounting	Recessed ceiling, single-sided
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Cut-Out	350mm x 48mm
Minimum Depth	80mm
Operating Mode	1.1kg
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running Man, Arrow Left
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	Battery
8011493	LED Strip
AUM01270340003 LUBPRO-CKIT-DALI	Driver Pack
8003060	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.