

CLEVERTRONICS L10 ULTRABLADE PRO



PRODUCT INFORMATION

Part Number	LUBPRO-UPS
Description	UPS Ultrablade Pro blade Exit. Supplied from a UPS (240VAC) or 220/240VAC/DC changeover supply (NOTE: change over facilities are required external to the luminaire supplied by others)
Construction	PC/ABS body with PC diffuser
Mounting	Recessed ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Ceiling Hole Cut-Out	350mm x 48mm
Minimum Ceiling Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	N/A - Manual test switch
Diffuser	All pictograph directional inserts included in the box
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E6.3 C ₉₀ =E6.3
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
8002178	PCA:LL-Pro L10 2pinML 60mA .#CT10142-L5
LUBPRO-CKIT-UPS	Ultrablade Pro,Control Only, L10 (UPS)

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

IMPORTANT NOTICE:

If there are separate supply cables coming to the fitting the contractor must install an additional, external changer over relay to facilitate the changeover from the 240V AC cables to the backup 240V AC cables. The fitting only has the capacity to accept one supply input.